



**80-125K**

# SOLARATOR SERIES

Operates Seamlessly with Generator: Experience Uninterrupted Power, Even in Areas with Grid Instability

## S6-EH3P(80-125)K10-NV-YD-H

Three Phase | High Voltage




- ### 12 Unique Advantages
- ★ Supports up to 2x rated PV input, maximizing solar energy utilization
  - ★ Supports a maximum string input current of 21A, ensuring compatibility with high-power PV modules
  - ★ Compatible with 100-314Ah battery modules, reducing overall system costs
  - ★ Supports fast battery charging with a maximum charging current of 200A
  - ★ Two independent battery ports for flexible configurations and easy capacity expansion
  - ★ Delivers 160% overload for 200ms in off-grid mode, ensuring stable startup of heavy loads
  - ★ Offers flexible control for weak grid and genset-hybrid scenarios, reducing investment costs
  - ★ SolisCloud: Smart remote control, AI optimisation, and instant troubleshooting - all in one platform
  - ★ Integrates PV and storage for demand management and anti-reverse flow functions
  - ★ Provides dynamic reactive power compensation to improve grid power factor and reduce reactive power charges
  - ★ Utility bypass function allows direct grid supply to backup loads
  - ★ Patented cooling technology ensures reliable operation even under high-temperature conditions

- ### 6 Leading Advantages
- Supports both DC and AC coupling, for flexible retrofits and system expansions
  - Ensures reliable backup power across diverse scenarios through battery reserve management
  - Extends supply time for critical loads with intelligent load prioritization
  - Offers a versatile three-in-one interface for seamless integration of on-grid PV, wind power, and diesel generators
  - Achieves on- and off-grid transitions in less than 10ms, ensuring an uninterrupted power supply
  - Supports multi-unit parallel operation up to 1.25MW (Solis STS cabinet recommended for systems over 6 units)

SRI LANKA

t: +86 574 6580 2188 (sales) +94 76 761 5759 (service)  
 e: sales@ginlong.com service@ginlong.com  
 w: solisinverters.com/lk



## DATASHEET

Models	80K	100K	125K
<b>Input DC (PV side)</b>			
Recommended max. PV array size	160 kW	200 kW	250 kW
Max. usable PV input power	160 kW	200 kW	250 kW
Max. input voltage		1000 V	
Rated voltage		600 V	
Start-up voltage		180 V	
MPPT voltage range		150 - 950 V	
Max. input current		10 × 42 A	
Max. short circuit current		10 × 60 A	
MPPT number / Max. input strings number		10 / 20	
<b>Battery</b>			
Battery type		Li-ion	
Battery voltage range		300 - 950 V	
Max. charge / discharge current		100 A × 2 / 100 A × 2	
Number of battery ports		2	
Max. charge / discharge current of each port		100 A	
Communication		CAN / RS485	
<b>Output AC (Back-up)</b>			
Rated output power	80 kW	100 kW	125 kW
Max. apparent output power		80-100K: 1.6 times of rated power, 10 s; 2 times of rated power, 200 ms; 125K: 1.4 times of rated power, 10 s; 1.6 times of rated power, 200 ms	
Back-up switch time		< 10 ms	
Rated output voltage		3/N/PE, 220 V / 380 V; 3/N/PE, 230 V / 400 V	
Rated frequency		50 Hz / 60 Hz	
THDv (@linear load)		< 3%	
<b>Input AC (Grid side)</b>			
Max. input current		250 A	
<b>Input AC (Generator)</b>			
Max. input power	80 kW	100 kW	125 kW
Rated input current	121.6 A / 115.5 A	151.9 A / 144.3 A	189.9 A / 180.4 A
Rated input voltage		3/N/PE, 220 V / 380 V; 3/N/PE, 230 V / 400 V	
Rated input frequency		50 Hz / 60 Hz	
<b>Output AC (Grid side)</b>			
Rated output power	80 kW	100 kW	125 kW
Max. apparent output power	80 kVA	100 kVA	125 kVA
Rated grid voltage		3/N/PE, 220 V / 380 V; 3/N/PE, 230 V / 400 V	
Rated grid frequency		50 Hz / 60 Hz	
Rated grid output current	121.6 A / 115.5 A	151.9 A / 144.3 A	189.9 A / 180.4 A
Power factor		> 0.99 (0.8 leading - 0.8 lagging)	
THDi		< 3%	
<b>Efficiency</b>			
Max. efficiency		97.5%	
EU efficiency	96.9%	97.1%	97.2%
BAT charged / discharged to AC max. efficiency		97.0%	
<b>Protection</b>			
Anti-islanding protection		Yes	
Output over current protection		Yes	
Short circuit protection		Yes	
Integrated DC switch		Yes	
DC reverse-polarity protection		Yes	
Protection class / Over voltage category		I/ DC II, AC III	
Surge protection		DC Type II / AC Type II	
Integrated AFCI 2.0		Optional	
<b>General Data</b>			
Max. power per phase (grid & back-up)	26.66 kW	33.33 kW	41.66 kW
Dimensions (W × H × D)		1174 × 814 × 400 mm	
Weight		170 kg	
Topology		Transformerless	
Operating ambient temperature range		-25 ~ +60°C	
Relative humidity		0 - 100%	
Ingress protection		IP66	
Cooling concept		Intelligent redundant fan-cooling	
Max. operation altitude		3000 m	
Grid connection standard <sup>①</sup>	G99, VDE-AR-N 4105/VDE V 0124, EN 50549-1&2/EN 50549-10, VDE 0126/UTE C 15/VFR:2019, NTS 631/RD 1699/ RD 244/UNE 206006/UNE 206007-1, CEI 0-21, C10/11, NRS 097-2-1, TOR, EIFS 2018.2, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530, MEA, PEA, PORTARIA Nº 140, DE 21 DE MARÇO DE 2022		
Safety / EMC standard <sup>①</sup>	IEC/EN 62109-1/-2, IEC/EN 61000-6-2/-4, EN 55011		
<b>Features</b>			
PV connection		MC4 Quick connection plug	
Battery connection		Terminal connector	
AC connection		Terminal block	
Display		7.0" LCD display & Bluetooth + APP	
Communication interface	Standard: WIFI+LAN+Bluetooth, CAN-BMS × 2, CAN-Parallel × 2, LAN, RS485-Meter, RS485, DRM, DI × 5, DO × 4; Optional: 4G		

<sup>①</sup> This column only shows the planned certification standards. Please confirm the specific time of obtaining the standards with the local team.