



Product Service

Compliance Document

No. D 086470 0210 Rev. 01

Holder of Certificate: **Ginlong Technologies Co., Ltd.**No.57 Jintong Road
Binhai Industrial Park, Xiangshan
315712 Ningbo, Zhejiang
PEOPLE'S REPUBLIC OF CHINA**Product:** **Converter**
Hybrid Inverter

This Compliance document confirms the compliance with the listed standards on a voluntary basis. It refers only to the sample submitted for testing and certification and does not certify the quality or safety of the serial products. For details see: www.tuvsud.com/ps-cert

Test report no.: 7040923048101-01**Date,** 2025-07-28

(Zhengdong Ma)



Product Service

Compliance Document

No. D 086470 0210 Rev. 01

Model(s): S6-EH1P9.9K03-NV-YD-L, S6-EH1P12K03-NV-YD-L, S6-EH1P14K03-NV-YD-L, S6-EH1P16K03-NV-YD-L, S6-EH1P18K03-NV-YD-L.

Parameters:

Model	S6-EH1P9.9K03-NV-YD-L	S6-EH1P12K03-NV-YD-L	S6-EH1P14K03-NV-YD-L
a). PV inputs			
Max. input voltage	DC 550 V		
MPP voltage range	DC 80, ..., 520 V		
Max. input current	DC 3x40 A		
Isc PV (absolute maximum)	DC 3x50 A		
b). Battery			
Battery type	Lithium-ion/Lead-acid		
Battery voltage range	DC 40, ..., 60 V		
Max. charge/discharge current	DC 208 A/208 A	DC 250 A/250 A	DC 290 A/290 A
c). AC-output (grid side)			
Rated output voltage	1/N/PE AC 230 V		
Rated output frequency	50 Hz		
Max. (Rated) output current	AC 43.1 A	AC 52.2 A	AC 60.9 A
Max. /Rated apparent output power	9900 VA	12000 VA	14000 VA
Displacement factor:	-0.8, ..., 1, ..., +0.8		



Product Service

Compliance Document

No. D 086470 0210 Rev. 01

Model	S6-EH1P16K03-NV-YD-L	S6-EH1P18K03-NV-YD-L
a). PV inputs		
Max. input voltage	DC 550 V	
MPP voltage range	DC 80, ..., 520 V	
Max. input current	DC 3x40 A	DC 3x42 A
Isc PV (absolute maximum)	DC 3x50 A	
b). Battery		
Battery type	Lithium-ion/Lead-acid	
Battery voltage range	DC 40, ..., 60 V	
Max. charge/discharge current	DC 290 A/290 A	DC 320 A/320 A
c). AC-output (grid side)		
Rated output voltage	1/N/PE AC 230 V	
Rated output frequency	50 Hz	
Max. (Rated) output current	AC 69.6 A	AC 78.2 A
Max. /Rated apparent output power	16000 VA	18000 VA
Displacement factor:	-0.8, ..., 1, ..., +0.8	

Tested according to:

IEC 61727:2004
IEC 62116:2014